

IN THE CLAIMS

1. (Currently amended) A method of routing traffic between first and second nodes in a network so as to provide protection against network failures, the method comprising the steps of:

routing units of traffic on corresponding sets of trunks connected between the first and second nodes such that the traffic is balanced between disjoint paths; and

implementing a restoration process for the traffic ~~utilizing at least one of service layer switching and transport layer switching;~~

the first and second nodes being connected by first and second sets of trunks such that the nodes and sets of trunks form a ring having at least four trunks, the first set of trunks being associated with one of an upper portion and a lower portion of the four-trunk ring, the second set of trunks being associated with the other of the upper portion and the lower portion of the four-trunk ring, wherein each of the first and second sets of trunks includes a primary trunk and a backup trunk;

a given one of the units of traffic comprising a unit of traffic to be transmitted in a direction from the first node to the second node utilizing one of the upper portion and the lower portion of the four-trunk ring;

~~wherein the routing step separates the given unit of traffic into at least first and second portions of substantially equal size;~~

~~wherein the routing step further comprises routing the given unit of traffic such that the at least first and second portions of the given unit of traffic are routed on respective first and second trunks of a corresponding set of trunks, the traffic in the given unit of traffic thereby being balanced between at least a pair of disjoint paths comprising the first and second trunks;~~

wherein the first and second nodes are configured to perform, in conjunction with the restoration process for the given unit of traffic, span switching between the primary trunk and the backup trunk of the associated portion of the four-trunk ring.

2. (Previously presented) The method of claim 1 wherein the given unit of traffic comprises one or more OC-x units of traffic.

3. (Currently amended) The method of claim 1 wherein the restoration process utilizes a service layer switching process ~~comprises~~ comprising a packet-based switching process.

4. (Currently amended) The method of claim 1 wherein the restoration process utilizes a service layer switching process ~~comprises~~ comprising an Internet protocol (IP) switching process.

5. (Currently amended) The method of claim 1 wherein ~~the first and second nodes are connected by first and second sets of trunks, each of the sets of trunks including multiple trunks, with each of the trunks in a given set of trunks~~ supporting supports a designated portion of at least one of the units of traffic.

6. (Currently amended) The method of claim 1 wherein the units of traffic are routed such that a first half of the given one of the units of traffic is routed on the first primary trunk, and a second half of the given unit is routed on the second backup trunk, in the associated portion of the four-trunk ring.

7. (Original) The method of claim 6 wherein the restoration process is implemented using service layer switching.

8. (Canceled)

9. (Canceled)

10. (Currently amended) The method of claim 9 1 wherein the ~~at least one given~~ unit of traffic is split equally between the primary trunk and the backup trunk of the associated ~~with the~~ upper or lower portion of the ring.

11. (Currently amended) The method of claim 9 1 wherein the ~~at least one~~ given unit of traffic is routed entirely on the primary trunk of the associated ~~with the~~ upper or lower portion of the ring.

12. (Currently amended) The method of claim 8 1 wherein the ring comprises an IP/optical hybrid ring, and the restoration process is implemented using service layer switching.

13. (Currently amended) The method of claim 8 1 wherein the ring comprises a SONET/optical ring, and the restoration process is implemented using transport layer switching.

14. (Currently amended) The method of claim ~~13~~ 1 wherein the first and second nodes comprise add-drop multiplexers connected by the sets of trunks, each of the add-drop multiplexers also being coupled to a corresponding router.

15. (Original) The method of claim 1 wherein the units of traffic are routed between the first and second nodes so as to provide an opportunity to implement an enhanced quality of service (QoS) for at least one of the units of traffic.

16. (Currently amended) An apparatus for routing traffic in a network so as to provide protection against network failures, the apparatus comprising:

first and second network nodes connected by sets of trunks, wherein units of traffic are each routed on a corresponding one of the sets of trunks such that the units of traffic are balanced between disjoint paths between the first and second nodes, the first and second nodes further being configured to implement a restoration process for the traffic ~~utilizing at least one of service layer switching and transport layer switching;~~

the first and second nodes being connected by first and second sets of trunks such that the nodes and sets of trunks form a ring having at least four trunks, the first set of trunks being associated with one of an upper portion and a lower portion of the four-trunk ring, the second set of

trunks being associated with the other of the upper portion and the lower portion of the four-trunk ring, wherein each of the first and second sets of trunks includes a primary trunk and a backup trunk;

a given one of the units of traffic comprising a unit of traffic to be transmitted in a direction from the first node to the second node utilizing one of the upper portion and the lower portion of the four-trunk ring;

~~wherein the given unit of traffic is separated into at least first and second portions of substantially equal size; and~~

~~wherein the given unit of traffic is routed such that the at least first and second portions of the given unit of traffic are routed on respective first and second trunks of a corresponding set of trunks, the traffic in the given unit of traffic thereby being balanced between at least a pair of disjoint paths comprising the first and second trunks;~~

wherein the first and second nodes are configured to perform, in conjunction with the restoration process for the given unit of traffic, span switching between the primary trunk and the backup trunk of the associated portion of the four-trunk ring.

17. (Currently amended) An apparatus for routing traffic in a network so as to provide protection against network failures, the apparatus comprising:

a first network node, the first node being connectable to at least a second network node by sets of trunks, wherein units of traffic are each routed on a corresponding one of the sets of trunks such that the units of traffic are balanced between disjoint paths between the first and second nodes, the first node further being configured to implement at least a portion of a restoration process for the traffic ~~utilizing at least one of service layer switching and transport layer switching;~~

the first and second nodes being connected by first and second sets of trunks such that the nodes and sets of trunks form a ring having at least four trunks, the first set of trunks being associated with one of an upper portion and a lower portion of the four-trunk ring, the second set of trunks being associated with the other of the upper portion and the lower portion of the four-trunk ring, wherein each of the first and second sets of trunks includes a primary trunk and a backup trunk;

a given one of the units of traffic comprising a unit of traffic to be transmitted in a direction from the first node to the second node utilizing one of the upper portion and the lower portion of the four-trunk ring;

~~wherein the given unit of traffic is separated into at least first and second portions of substantially equal size; and~~

~~wherein the given unit of traffic is routed such that the at least first and second portions of the given unit of traffic are routed on respective first and second trunks of a corresponding set of trunks, the traffic in the given unit of traffic thereby being balanced between at least a pair of disjoint paths comprising the first and second trunks;~~

wherein the first and second nodes are configured to perform, in conjunction with the restoration process for the given unit of traffic, span switching between the primary trunk and the backup trunk of the associated portion of the four-trunk ring.